

Specification sheet

CF 370

FA 4X2 Rigid



067F8709AAAA - 202217B - 14-01-2022

ENGINES
CF 370 MX-11 (270 kW / 367 hp)
CF 410 MX-11 (300 kW / 408 hp)
CF 450 MX-11 (330 kW / 449 hp)
CF 430 MX-13 (315 kW / 428 hp)
CF 480 MX-13 (355 kW / 483 hp)
CF 530 MX-13 (390 kW / 530 hp)

GVM ¹⁾	GCM ²⁾
19000 kg	40000 kg
Max. front 7000 kg	
Max. rear 13000 kg	

Greece, ERGOTRAK, www.daftrucks.gr

CAB EXTERIOR

Day Cab with galvanised steel bumper, tinted glass and electric window openers. Main mirrors and wide angle mirrors electrically heated. Cab width 2300 mm.; LED daytime running lights; Electrically adjustable mirrors; Front view mirror.

Optional

02106	Sleeper Cab	09983	Fog lights
01137	Space Cab	09984	Fog lights and cornering lights
01226	Cab suspension air	06593	Skylights
01174	External sun visor green translucent	06628	One hazard beacon light at co-driver side
00847	Air horns, single set	06627	One hazard beacon light at driver side
09006	Air horns, double set	06629	Two hazard beacon lights
08020	LED head lights		

AERODYNAMICS

Optional

06776	Adjustable roof air deflector	04906	Side collars
-------	-------------------------------	-------	--------------

COLOURS

Cab colour H3279 Brilliant White; Head lamp panel and bumper: Brilliant White; Chassis colour grey..

Optional

06485	Head lamp panel and bumper: cab colour	09933	Head lamp panel and bumper: Stone Grey
-------	--	-------	--

CAB INTERIOR

Cab interior trim colour Dark Sand; Cab interior decoration Black Rock; Driver seat: Comfort Air; Co-driver seat: basic; Automatic Temperature Control and airco; Pollen filter; Roof hatch glass, manual control.

Optional

09271	Steering wheel, leather, colour black	07746	Co-driver seat: Super Air
07240	Steering wheel, leather, Exclusive	07748	Co-driver seat: Xtra Leather Air
07152	Cab interior trim colour Exclusive	00967	Seat belts red
07592	Cab interior decoration Argenta	02117	Third seat
07591	Cab interior decoration Rustica	06539	Refrigerator
07733	Driver seat: Luxury Air	06783	Lower bunk foam mattress
07736	Driver seat: Super Air	06784	Lower bunk mattress Xtra Comfort
07737	Driver seat: Xtra Leather Air	06676	PL light in cab ceiling
07741	Co-driver seat: Comfort Air	06970	Automatic Cab Climate Control
07743	Co-driver seat: Luxury Air		

COMMUNICATION AND DRIVING MANAGEMENT

Tachograph digital, Stoneridge 1C; Speed limiter setting 85 km/h; Eco off 90 km/h; Antennas: radio, 2x cellular, GNSS; Adaptive Cruise Control with FCW and AEBS-3.

Optional

09681	Preparation for Maut	07261	TruckPhone
08450	Luxury speaker system with 6 speakers	06991	Predictive Cruise Control
07117	Radio/USB player, 2 speakers	06992	Predictive Cruise Control lite

SAFETY AND SECURITY

Lane Departure Warning System; Vehicle Stability Control (VSC); Basic engine immobiliser system.

Optional

08631	Air bag (driver) and 2 seat belt tensioners	09827	Side camera system
09828	Front camera system	01725	Reverse warning

SUSPENSION AND AXLES

Front axle load 8.00 t; Rear: 13.00 t, air suspension, SR1344.

Optional

06257	Front axle load 9.00 t	04588	Rear axle SR1347
04647	Front springs air	01603	Rear springs parabolic
04057	Rear axle HR1356	08191	Axle load monitoring

WHEELS AND TYRES

Front axle(s): 315/70R22.5; Driven rear axle(s): 315/70R22.5; Disc wheels steel, silvergrey; Wheel protection rings silvergrey.

Optional

16152	Tyre makes and types
-------	----------------------

DRIVELINE

Engine MX-11, multi torque 6 cylinder diesel engine, 10.8 litres. Output 270 kW (367 hp) at 1600 rpm. Maximum torque 1900 Nm at 900-1125 rpm.; Exhaust emission Euro 6; Engine idle shutdown, 5 minutes; Automated gearbox, TraXon, 12 speeds; Gearbox ratio 16.69-1.00; Rear axle ratio 2.38.

Optional

04523	Manual gearbox, 16 speeds	07103	Automated gearbox, TraXon, 16 speeds
-------	---------------------------	-------	--------------------------------------

BRAKE SYSTEM

Exhaust brake; Ventilated disc brakes front and rear. Dual circuit air system with electronic control (EBS). Twin cylinder air compressor with heated dryer and economy mode..

Optional

09921	MX Engine Brake	04901	Spring brake cylinders on the first front axle
02715	ZF Intarder		

CHASSIS

Wheelbase 4.20 m / rear overhang 1.80 m; Side member height 310 mm; Standard component location; Exhaust pipe horizontal, low; Aluminium fuel tank 340 l, height 620 mm; Tank for AdBlue® 45 l, left-hand side chassis; Front underrun protection (FUP); Spray suppression.

Optional

02393	Side member height 260 mm	07071	Spare wheel carrier right-hand side
06611	Exhaust pipe vertical, high	03323	Rear light with LEDs

DRAWBAR AND TRAILER EQUIPMENT

D-value cross member D=13.7; Pneumatic trailer connection palm type; Electric connection 24 V / 2x7 pins.

Optional

07033	Trailer coupling Ringfeder D=13.7	08027	Trailer coupling Rockinger D=20.0
07034	Trailer coupling Ringfeder D=20.0	04624	Closing member
08026	Trailer coupling Rockinger D=13.0	07032	D-value cross member D=20

BODIES AND PREPARATIONS FOR BODYING

Application connector on the cab front.

Optional

04331	Appl connector including air control prep	06692	Application connector chassis
09050	Application connectors for bb remote control	02597	Application connector for tail lift control

POWER TAKE-OFF (PTO)

Optional

16148 PTO types and positions

ELECTRICAL POWER SUPPLY

Alternator 80 A, batteries 2x 175 Ah..

Optional

06460	Alternator 120 A	07671	Batteries 2x210Ah AGM C-type
08775	Alternator 150 A	06440	Batteries 2x230Ah
01257	Batteries 2x140Ah		

GVM AND GCM

Chassis weight related technical GVM max 20500 kg; Driveline related max GCM 40000 kg class 3.

Optional

00200	Driveline related max GCM 38000 kg class 2	00939	Driveline related max GCM 56000 kg class 2
03673	Driveline related max GCM 44000 kg class 2	00818	Driveline related max GCM 60000 kg class 3
03675	Driveline related max GCM 50000 kg class 3		

APPLICATION CONDITIONS

Air intake on the cab roof.

Optional

08400	Silent mode	09961	Cyclonic air intake behind the cab
-------	-------------	-------	------------------------------------

SERVICE AND MAINTENANCE

Warranty Plus - Driveline, takes care of 1 year complete vehicle (excl. real wear parts), 2nd and 3rd year driveline up to 500,000 km and 1st year breakdown.; ITS service.

Optional


08311 Service interval extended



Go to [DAF.com](https://www.daf.com) to configure your own perfect DAF.

CF 370

FA 4X2 Rigid



		Wheelbase - AE			Unladen weight ¹⁾			Gross Carrying Capacity			Variable dimensions									
		WB	AE ⁵⁾		Front	Rear	Total	Front	Rear	Total	AC	CB ⁶⁾	CH ⁷⁾	BL ⁸⁾	BL	TL	HA ⁹⁾	HA ¹⁰⁾	TK ¹¹⁾	TW ¹²⁾
DAY CAB	3.80	1.30	4521	1735	6256	2479	11265	12744	0,39	0,18	1,99	4,99	5,58	6,47	0,97	0,95	13,50	14,85		
	4.00	1.70	4497	1846	6343	2503	11154	12657	0,39	0,18	1,94	5,28	5,91	7,07	1,02	0,99	14,01	15,37		
	4.20	1.80	4504	1871	6374	2496	11129	12626	0,39	0,18	1,94	5,61	6,26	7,37	1,02	0,99	14,53	15,90		
	4.50	1.95	4517	1914	6431	2483	11086	12569	0,39	0,18	1,94	6,09	6,79	7,82	1,02	0,99	15,31	16,69		
	4.70	2.05	4517	1932	6449	2483	11068	12551	0,39	0,18	1,94	6,41	7,14	8,12	1,02	0,99	15,83	17,22		
	4.90	2.15	4518	1949	6467	2482	11051	12533	0,39	0,18	1,94	6,72	7,50	8,42	1,02	0,99	16,35	17,75		
	5.10	2.30	4517	1971	6487	2483	11029	12513	0,39	0,18	1,94	7,04	7,85	8,77	1,02	0,99	16,87	18,28		
	5.40	2.40	4525	1992	6517	2475	11008	12483	0,39	0,18	1,94	7,53	8,38	9,17	1,02	1,00	17,66	19,07		
	5.70	2.30	4538	1995	6533	2462	11005	12467	0,39	0,18	1,94	8,02	8,91	9,37	1,02	1,00	18,44	19,86		
	6.10	2.55	4549	2041	6590	2451	10959	12410	0,39	0,18	1,94	8,65	9,62	10,02	1,02	1,00	19,49	20,92		
SLEEPER CAB	6.60	2.85	4640	2201	6841	2360	10799	12159	0,39	0,18	1,94	9,51	10,58	10,82	1,02	1,00	20,80	22,24		
	6.90	3.00	4649	2231	6879	2351	10769	12121	0,39	0,18	1,94	9,99	11,11	11,27	1,02	1,00	21,59	23,04		
	3.80	1.30	4565	1748	6313	2435	11252	12687	0,82	0,16	1,99	4,18	4,78	6,47	0,97	0,94	13,50	14,85		
	4.00	1.70	4542	1858	6399	2458	11142	12601	0,82	0,16	1,94	4,49	5,11	7,07	1,02	0,99	14,01	15,37		
	4.20	1.80	4549	1882	6431	2451	11118	12569	0,82	0,16	1,94	4,80	5,47	7,37	1,02	0,99	14,53	15,90		
	4.50	1.95	4563	1925	6487	2437	11075	12513	0,82	0,16	1,94	5,29	6,00	7,82	1,02	0,99	15,31	16,69		
	4.70	2.05	4563	1942	6505	2437	11058	12495	0,82	0,16	1,94	5,61	6,35	8,12	1,02	0,99	15,83	17,22		
	4.90	2.15	4565	1959	6524	2435	11041	12476	0,82	0,16	1,94	5,93	6,71	8,42	1,02	0,99	16,35	17,75		
	5.10	2.30	4564	1980	6544	2436	11020	12456	0,82	0,16	1,94	6,25	7,06	8,77	1,02	0,99	16,87	18,28		
	5.40	2.40	4572	2001	6573	2428	10999	12427	0,82	0,16	1,94	6,73	7,59	9,17	1,02	0,99	17,66	19,07		
SPACE CAB	5.70	2.30	4586	2003	6589	2414	10997	12411	0,82	0,16	1,94	7,22	8,14	9,37	1,02	0,99	18,44	19,86		
	6.10	2.55	4598	2049	6647	2402	10951	12353	0,82	0,16	1,94	7,88	8,84	10,02	1,02	0,99	19,49	20,92		
	6.60	2.85	4689	2208	6897	2311	10792	12103	0,82	0,16	1,94	8,73	9,80	10,82	1,02	0,99	20,80	22,24		
	6.90	3.00	4698	2237	6936	2302	10763	12064	0,82	0,16	1,94	9,21	10,34	11,27	1,02	0,99	21,59	23,04		
	3.80	1.30	4677	1747	6425	2323	11253	12575	0,82	0,16	2,67	4,24	4,83	6,47	0,97	0,94	13,50	14,85		
	4.00	1.70	4654	1858	6511	2346	11142	12489	0,82	0,16	2,62	4,55	5,17	7,07	1,02	0,99	14,01	15,37		
	4.20	1.80	4661	1882	6543	2339	11118	12457	0,82	0,16	2,62	4,86	5,53	7,37	1,02	0,99	14,53	15,90		
	4.50	1.95	4675	1925	6599	2325	11075	12401	0,82	0,16	2,62	5,36	6,08	7,82	1,02	0,99	15,31	16,69		
	4.70	2.05	4675	1942	6617	2325	11058	12383	0,82	0,16	2,62	5,68	6,43	8,12	1,02	0,99	15,83	17,22		
	4.90	2.15	4677	1959	6636	2323	11041	12364	0,82	0,16	2,62	6,00	6,78	8,42	1,02	0,99	16,35	17,75		
SPACE CAB	5.10	2.30	4676	1980	6656	2324	11020	12344	0,82	0,16	2,62	6,32	7,13	8,77	1,02	0,99	16,87	18,28		
	5.40	2.40	4685	2001	6685	2315	10999	12315	0,82	0,16	2,62	6,81	7,67	9,17	1,02	0,99	17,66	19,07		
	5.70	2.30	4698	2003	6701	2302	10997	12299	0,82	0,16	2,62	7,31	8,22	9,37	1,02	0,99	18,44	19,86		
	6.10	2.55	4710	2049	6759	2290	10951	12241	0,82	0,16	2,62	7,97	8,95	10,02	1,02	0,99	19,49	20,92		
	6.60	2.85	4801	2208	7009	2199	10792	11991	0,82	0,16	2,62	8,83	9,92	10,82	1,02	0,99	20,80	22,24		
	6.90	3.00	4810	2237	7048	2190	10763	11952	0,82	0,16	2,62	9,32	10,46	11,27	1,02	1,00	21,59	23,04		

OTHER DIMENSIONS	VA: 1,37	HV ¹³⁾ : 1,03	HV ¹⁴⁾ : 0,96	RB: 0,79	SB: 1,82	TB ¹⁵⁾ : 2,48
------------------	----------	--------------------------	--------------------------	----------	----------	--------------------------

1) GVM in conformity with registration documents.

2) GCM in conformity with registration documents.

3) Axle load with standard tyre size.

4) Chassis and cab weight calculated with: Standard specification items only with 0 litres of fuel, 0 litres of AdBlue® and driver of 75 kg, tolerance ± 3%. Changing of the specification can have major impact on vehicle weight.

5) Other AE dimensions may be available for shown WB. Modify rear overhang to the calculated body length.

6) CB is based on standard air intake and/or exhaust.

7) Cab height is measured from frame member to closed cabin roof hatch.

8) Calculate customer specific body length with TOPEC. Body lengths shown based on evenly distributed load at max axle load.

9) Unladen height at centre of driven axle(s).

10) Laden height at centre of driven axle(s).

11) TK = turning circle between kerbs.

12) TW = turning circle between walls.

13) Unladen height at centre of front axle(s).

14) Laden height at centre of front axle(s).

15) TB is overall width at rear. (At lower cab step 255).

Depending on the vehicle configuration a specific option may not be possible. The availability and specification of this vehicle may differ per country. For further information please contact the DAF organisation. Pictures and technical illustrations are not binding in detail and can differ from the standard specification. Subject to modification without prior notice.